


## NEW PRODUCT INFORMATION

### New super-bright Through-hole & SMD-LEDs - 525nm green



#### Features

- Low power consumption
- Forward voltage true green = typ. 3,3V - max. 4,1V
- RoHS compliant

Part number	Package	Lens type	lv (mcd) @ 20mA		Viewing angle
			min.	typ.	
L-7104ZGCK	3mm	water-clear	5000	8000	34°
L-7104ZGDK	3mm	green-diffused	650	1300	40°
L-7113ZGCK	5mm	water-clear	7000	12000	20°
L-7113ZGDK	5mm	green-diffused	700	1200	30°
KP-1608ZGCK	0603	water-clear	200	350	120°
KPT-1608ZGCK	0603 Super Thin	water-clear	200	350	120°
KP-2012ZGCK	0805	water-clear	200	350	120°
KPT-2012ZGCK	0805 Super Thin	water-clear	200	350	120°
KP-3216ZGCK	1206	water-clear	200	350	120°
KPT-3216ZGCK	1206 Super Thin	water-clear	200	350	120°
KPTD-3216ZGCK	1206 Dome Lens	water-clear	1300	2100	35°
KA-3528ZGCKT	PLCC-2	water-clear	300	500	120°
KPA-1606ZGCK	0602 Right Angle	water-clear	200	300	110°
KPA-3010ZGCK	1104 Right Angle	water-clear	200	300	120°

Luminous intensity value is traceable to the CIE 120-2007 compliant national standards

Head office in Germany:

Lindenau 7 / Gewerbegebiet  
D-47661 Issum  
Tel. +49 (2835) 4446-0  
Fax +49 (2835) 4446-29  
info@kingbright-europe.de

Branch office in France:

33 rue Benoit Malon  
F-92150 SURESNES  
Tel. +33 01.71.12.61.28  
Fax +33 01.71.12.61.36  
info@kingbright-europe.fr

[www.kingbright-europe.de](http://www.kingbright-europe.de)